



Kunststoff- schrauben

DIN 84 (ISO 1207)

Zylinderschraube mit Schlitz

Werkstoff: Polyamid PA 6.6

- Zugfestigkeit 60–80 N/mm², je nach Wassergehalt.
- Beständig gegen Mineralöle und schwache Laugen.
- Temperaturbeständig von –40°C bis +120°C, kurzzeitig bis +150°C.
- Wasseraufnahme 8–10%.

Nenn-Ø d	M 3	M 4	M 5	M 6	M 8
d _k mm	5,5	7,0	8,5	10,0	13,0
k mm	2,0	2,6	3,3	3,9	5,0
n mm	0,8	1,0	1,2	1,2	2,0
t mm	0,85	1,1	1,3	1,6	2,0

Nenn-Ø d	Länge l mm	PA 6.6		VE/St.
		Art.-Nr.		
M 3	4	0278 3 4	1000	
	6	0278 3 6	100	
	8	0278 3 8		
	10	0278 3 10		
	12	0278 3 12		
	16	0278 3 16		
	20	0278 3 20		
	22	0278 3 22	1000	
30	0278 3 30			
M 4	6	0278 4 6	100	
	8	0278 4 8		
	10	0278 4 10		
	12	0278 4 12		
	16	0278 4 16		
	20	0278 4 20		
	25	0278 4 25		
	30	0278 4 30		
50	0278 4 50			
M 5	8	0278 5 8	100	
	10	0278 5 10		
	12	0278 5 12		
	16	0278 5 16		
	18	0278 5 18	1000	
	20	0278 5 20	100	
	25	0278 5 25		
	30	0278 5 30		
40	0278 5 40			
M 6	10	0278 6 10	100	
	12	0278 6 12		
	16	0278 6 16		
	20	0278 6 20		
	25	0278 6 25		
	30	0278 6 30		
	40	0278 6 40		
M 8	10	0278 8 10	1000	
	30	0278 8 30	100	